



CED 750
CORE DRILL RIG

# 01.

#### **Power Unit**

Mfg CUMMINS

Model 4BTA - 4 Cylinder

Power 120 HP

**Rpm** 2200

Engine Type Diesel

Cooling Water



## 02.

### Hydraulic System

**Primary Pump** 

**Secondary Pump** 

Hydraulic Oil Cooling

Main Valve Bank

**Auxiliary Valve Bank** 

Hydraulic Return Filter

Hydraulic Inlet Strainer

Variable Piston Pump

Gear Pump

Water Cooling & Air Blast

**Directional Valve Control** 

**Directional Valve Control** 



At CED, we provide reliable drilling solutions. Wherever your exploration leads.

### 03.

### Drill Head & Spindle

**Power** 

Gearbox

Spindle Speed

**Top Swivel** 

Variable Speed Control

Hydraulic Head Sliding Away

Variable Piston Pump

Gear Pump

Water Cooling & Air Blast

0 - 600 RPM



04.

Wireline

Capacity 800m

Cable Size 6mm (1/4")

Wireline Motor Eaton 2000 Series

05.

Depth Capacity

**NQ** 750m

HQ 400m

PQ 150m

06.



Mast & Feed System

Mast2 SectionFeed Travel3.2mRod Pull Length6m

Mast Dump 1.2m

 Feed speed fast and slow with variable control

• Feed pressure adjustment

Drilling angle 45 to 90 degrees

07.

### Standard Equipment

**Hydraulic Breakout** 

UDR Foot Clamp (NQ - HQ)

Hydraulic Oil Tank

**Fuel Tank** 

Spin Guard

**Emergency Stop Button** 

Cross Over Sub NQ, HQ & PQ Pin

Main Host

Shut Down System **Battery Isolator** 

08.

#### **Drill Pump**

Yanmar TF190R **Engine** 

Starter Electric

CDS TP135 (435) Mud Pump

**Belt Drive** 

Safety Guard

Bean Relief Valve

**Battery Box** 

**Battery** 



Complete with all adaptor, 6m suction hose, camlock & foot valve

Hydraulic driven planetary winch, with static break Single line capacity bare drum 6000 kg

Ready to Partner with Us?

Contact us today to learn more about our products and how we can help you succeed!

**%** +27 796650705

+44 7591 811002

www.cylinder-ed.com info@cylinder-ed.com